



ORIENTAL
SEMICONDUCTOR

GreenMOS™

OSG55R190xF_Datasheet

Green
PRODUCT

RoHS
compliant

Enhancement Mode N-Channel Power MOSFET

Features

- ◆ Low $R_{DS(on)}$ & FOM
- ◆ Extremely low switching loss
- ◆ Excellent stability and uniformity
- ◆ Easy to drive

Applications

- ◆ Lighting
- ◆ Hard switching PWM
- ◆ Server power supply
- ◆ Charger




■ General Description

OSG55R190xF uses advanced GreenMOS™ technology to provide low $R_{DS(ON)}$, low gate charge, fast switching and excellent avalanche characteristics. This device is suitable for active power factor correction and switching mode power supply applications.

◆ V_{DS} , min@ T_{jmax}	600 V
◆ I_D , pulse	60 A
◆ $R_{DS(ON)}$, max @ $V_{GS}=10$ V	190 mΩ
◆ Q_g	17.7 nC

■ Schematic and Package Information



■ Absolute Maximum Ratings at $T_j=25^\circ\text{C}$ unless otherwise noted

Parameter	Symbol	Value	Unit
Drain source voltage	V_{DS}	550	V
Gate source voltage	V_{GS}	± 30	V
Continuous drain current ¹⁾ , $T_c=25^\circ\text{C}$	I_D	20	A
Continuous drain current ¹⁾ , $T_c=100^\circ\text{C}$		12.5	
Pulsed drain current ²⁾ , $T_c=25^\circ\text{C}$	$I_{D, \text{pulse}}$	60	A
Power dissipation ³⁾ for TO251, TO252, TO220, $T_c=25^\circ\text{C}$	P_D	104	W
Power dissipation ³⁾ for TO220F, $T_c=25^\circ\text{C}$		32	
Single pulsed avalanche energy ⁵⁾	E_{AS}	200	mJ
MOSFET dv/dt ruggedness, $V_{DS}=0...440$ V	dv/dt	50	V/ns
Reverse diode dv/dt, $V_{DS}=0...440$ V, $I_{SD} \leq I_D$	dv/dt	15	V/ns
Operation and storage temperature	T_{stg}, T_j	-55 to 150	°C



■ Thermal Characteristics

Parameter	Symbol	Value	Unit
Thermal resistance, junction-case	$R_{\theta JC}$	3.9	°C/W
Thermal resistance, junction-ambient ⁴⁾	$R_{\theta JA}$	62.5	°C/W

■ Electrical Characteristics at $T_j=25$ °C unless otherwise specified

Parameter	Symbol	Min.	Typ.	Max.	Unit	Test condition
Drain-source breakdown voltage	BV_{DSS}	550			V	$V_{GS}=0$ V, $I_D=250$ μA
		600				$V_{GS}=0$ V, $I_D=250$ μA, $T_j=150$ °C
Gate threshold voltage	$V_{GS(th)}$	2.7		3.7	V	$V_{DS}=V_{GS}$, $I_D=250$ μA
Drain-source on-state resistance	$R_{DS(ON)}$		0.15	0.19	Ω	$V_{GS}=10$ V, $I_D=10$ A
			0.37			$V_{GS}=10$ V, $I_D=10$ A, $T_j=150$ °C
Gate-source leakage current	I_{GSS}			100	nA	$V_{GS}=30$ V
				-100		$V_{GS}=-30$ V
Drain-source leakage current	I_{DSS}			1	μA	$V_{DS}=550$ V, $V_{GS}=0$ V

■ Dynamic Characteristics

Parameter	Symbol	Min.	Typ.	Max.	Unit	Test condition
Input capacitance	C_{iss}		991.4		pF	$V_{GS}=0$ V, $V_{DS}=50$ V, $f=100$ kHz
Output capacitance	C_{oss}		125.9		pF	
Reverse transfer capacitance	C_{rss}		2.7		pF	
Turn-on delay time	$t_{d(on)}$		22.0		ns	$V_{GS}=10$ V, $V_{DS}=400$ V, $R_G=2$ Ω, $I_D=10$ A
Rise time	t_r		6.7		ns	
Turn-off delay time	$t_{d(off)}$		36.1		ns	
Fall time	t_f		3.5		ns	

■ Gate Charge Characteristics



Parameter	Symbol	Min.	Typ.	Max.	Unit	Test condition
Total gate charge	Q_g		17.7		nC	$I_D=10\text{ A}$, $V_{DS}=400\text{ V}$, $V_{GS}=10\text{ V}$
Gate-source charge	Q_{gs}		4.0		nC	
Gate-drain charge	Q_{gd}		7.2		nC	
Gate plateau voltage	$V_{plateau}$		5.7		V	

■ Body Diode Characteristics

Parameter	Symbol	Min.	Typ.	Max.	Unit	Test condition
Diode forward current	I_S			20	A	$V_{GS} < V_{th}$
Pulsed source current	I_{SP}			60		
Diode forward voltage	V_{SD}			1.3	V	$I_S=20\text{ A}, V_{GS}=0\text{ V}$
Reverse recovery time	t_{rr}		237.7		ns	$V_R=400\text{ V}, I_S=10\text{ A}$, $di/dt=100\text{ A}/\mu\text{s}$
Reverse recovery charge	Q_{rr}		2.6		μC	
Peak reverse recovery current	I_{rrm}		21.1		A	

■ Note

- 1) Calculated continuous current based on maximum allowable junction temperature.
- 2) Repetitive rating; pulse width limited by max. junction temperature.
- 3) P_d is based on max. junction temperature, using junction-case thermal resistance.
- 4) The value of $R_{\theta JA}$ is measured with the device mounted on 1 in 2 FR-4 board with 2oz. Copper, in a still air environment with $T_a=25\text{ }^{\circ}\text{C}$.
- 5) $V_{DD}=100\text{ V}$, $R_G=25\text{ }\Omega$, $L=10\text{ mH}$, starting $T_j=25\text{ }^{\circ}\text{C}$.



■ Electrical Characteristics Diagrams




Figure 1, Typ. output characteristics




Figure 2, Typ. transfer characteristics




Figure 3, Typ. capacitances




Figure 4, Typ. gate charge




Figure 5, Drain-source breakdown voltage




Figure 6, Drain-source on-state resistance




Figure 7, Threshold voltage




Figure 8, Forward characteristic of body diode




Figure 9, Drain-source on-state resistance






Figure 10, Drain current

Figure 11, Safe operation area for
TO251/TO252/TO220 $T_c = 25^\circ\text{C}$ Figure 11, Safe operation area for TO220
 $T_c = 25^\circ\text{C}$



■ Test circuits and waveforms




Figure 1, Gate charge test circuit & waveform




Figure 2, Switching time test circuit & waveforms




Figure 3, Unclamped inductive switching (UIS) test circuit & waveforms





Figure 4, Diode reverse recovery test circuit & waveforms



■ Package Information


Figure1, TO251 package outline dimension





■ Package Information


Figure2, TO252 package outline dimension






■ Package Information

Figure3, TO220F package outline dimension



**■ Package Information**

Figure4, TO220 package outline dimension



**■ Ordering Information**

Package	Units/Tube	Tubes/Inner Box	Units/Inner Box	Inner Box/Carton Box	Units/Carton Box
TO251	75	66	4950	6	29700
TO220F	50	20	1000	6	6000
TO220	50	20	1000	6	6000

Package	Units/Tape	Tapes/Inner Box	Units/Inner Box	Inner Box/Carton Box	Units/Carton Box
TO252	2500	2	5000	5	25000

■ Product Information

Product	Package	Pb Free	RoHS	Halogen Free
OSG55R190AF	TO251	yes	yes	yes
OSG55R190DF	TO252	yes	yes	yes
OSG55R190FF	TO220F	yes	yes	yes
OSG55R190PF	TO220	yes	yes	yes